

Follow these instructions if pairing is successful from the start.

Programming Symbol LS4278 – Bluetooth Barcode Scanner USB

Connect one end (data end) of the synapse cable to the cradle and the other end to the (USB end) host computer.

SCAN - USB HOST TYPE – HID Keyboard Emulation – Quick Reference Guide Pg. 10

SCAN – I 2 of 5 Any length – Product Reference Guide 13-35

SCAN – Carriage Return Line Feed – SCAN OPTIONS/DATA SUFFIX/ENTER – Quick Reference Guide Pg. 13

Programming Symbol LS4278 – Bluetooth Barcode Scanner PS2 (KBW)

Connect one end (data end) of the synapse cable to the cradle, the other end follows a PS2 male and female connector. Male PS2 connects to the host computer PS2 port and the female PS2 connects to the keyboard cable.

SCAN – Keyboard Wedge Host Type – IBM PC/AT and IBM PC Compatibles. Quick Reference Guide Pg. 7

SCAN – I 2 of 5 Any length – Product Reference Guide 13-35

SCAN – Carriage Return Line Feed – SCAN OPTIONS/DATA SUFFIX/ENTER – Quick Reference Guide Pg. 13

Troubleshooting:

If pairing is unsuccessful follow these instructions:

SCAN – Set Defaults – Quick Reference Guide Pg. 6

SCAN – Enable Pair On Contacts – Quick Reference Guide Pg. 13 – **placed the scanner on the cradle after scanning and wait for it to beep and pair.**

SCAN the **correct** Host Type either USB or PS2 (kbw).

SCAN – I 2 of 5 Any length – Product Reference Guide 13-35

SCAN – Carriage Return Line Feed – SCAN OPTIONS/DATA SUFFIX/ENTER – Quick Reference Guide Pg. 13